Program Complot
(Version 2018-1)
by
Dermott E. Cullen
(Present Contact Information)
Dermott E. Cullen
1466 Hudson Way
Livermore, CA 94550
U.S.A.
Tele: 925-443-1911
E.Mail:redcullen1@comcast.net
Web:redcullen1.net/HOMEPAGE.NEW

Press Mouse Button to Start


MAT 5231
Total
Cross Section
52-Te-122
-91.82 To 1954. %
Max
Ratio
Min
Ratio
TENDL
ENDFB8.0
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
1
52-Te-122


MAT 5231
Elastic
Cross Section
52-Te-122
-99.16 To 9999. %
Max Ratio
Min Ratio
TENDL
ENDFB8.0
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
2
52-Te-122


MAT 5231
Inelastic
Cross Section
52-Te-122
-78.04 To -17.84%
Max
Ratio
Min
Ratio
TENDL Threshold 568.76 keV
ENDFB8.0 Threshold 568.67 keV
Cross Section (barns)
2.5
2.0
1.5
1.0
0.5
0.0
ENDFB8.0/TENDL
Ratio
1.0
0.8
0.6
0.4
0.2
6 7 8
10^6
2
3
4
5
6
7
8
10^7
2
3
4
5
6
7
8
10^8
2
3
Incident Energy (eV)
52-Te-122


MAT 5231
(n,2n)
Cross Section
52-Te-122
-59.39 To 41.66 %
Max
Ratio
TENDL Threshold 9.9217 MeV
ENDFB8.0 Threshold 10.000 MeV
Cross Section (barns)
1.8
1.6
1.4
1.2
1.0
0.8
0.6
0.4
0.2
0.0
ENDFB8.0/TENDL
Ratio
1.6
1.2
0.8
0.4
10^7
2
3
4
5
6
7
8
9
10^8
2
4
Incident Energy (eV)
52-Te-122


MAT 5231
(n,3n)
Cross Section
52-Te-122
313.6 To 864.9 %
Min
Ratio
TENDL Threshold 17.231 MeV
ENDFB8.0 Threshold 17.193 MeV
Cross Section (barns)
1.0
0.8
0.6
0.4
0.2
0.0
ENDFB8.0/TENDL
Ratio
10
8
6
4
2
3
4
5
6
7
8
9
10^8
2
5
Incident Energy (eV)
52-Te-122


MAT 5231
(n,n') α
Cross Section
52-Te-122
-90.53 To 9999. %
Min Ratio
Max Ratio
TENDL Threshold 1.0955 MeV
ENDFB8.0 Threshold 1.2082 MeV
Cross Section (milli-barns)
35
30
25
20
15
10
5
0
ENDFB8.0/TENDL
Ratio
10^4
10^2
10^0
2 3 4 5 6 7 8
10^7
2 3 4 5 6 7 8
10^8
2
6
Incident Energy (eV)
52-Te-122


MAT 5231
(n,n') p
Cross Section
52-Te-122
-100.0 To 6.687 %
Min Ratio
Max Ratio
TENDL Threshold 8.0693 MeV
ENDFB8.0 Threshold 9.0000 MeV
Cross Section (milli-barns)
80
60
40
20
0
ENDFB8.0/TENDL
Ratio
10^0
10^-3
10^-6
10^-9
8 9 10^7 2 3 4 5 6 7 8 9 10^8 2
7
Incident Energy (eV)
52-Te-122


MAT 5231
MT= 51 (n,n') Level
Cross Section
52-Te-122
-100.0 To -19.42%
Max
Ratio
Min
Ratio
TENDL Threshold 568.76 keV
ENDFB8.0 Threshold 568.67 keV
Cross Section (barns)
1.4
1.2
1.0
0.8
0.6
0.4
0.2
0.0
ENDFB8.0/TENDL
Ratio
10^0
10^-3
10^-6
10^-9
6 7 8
10^6
2 3 4 5 6 7 8
10^7
2 3 4 5 6 7 8
10^8
2
8
Incident Energy (eV)
52-Te-122


MAT 5231
MT= 52 (n,n') Level
Cross Section
52-Te-122
-100.0 To 33.56 %
Max
Ratio
Min
Ratio
TENDL Threshold 1.1910 MeV
ENDFB8.0 Threshold 1.1901 MeV
Cross Section (milli-barns)
200
150
100
50
0
ENDFB8.0/TENDL
Ratio
10^0
10^-3
10^-6
10^-9
2 3 4 5 6 7 8
10^7
2 3 4 5 6 7 8
10^8
2
9
Incident Energy (eV)
52-Te-122


MAT 5231
MT= 53 (n,n') Level
Cross Section
52-Te-122
-100.0 To 23.05 %
Max
Ratio
Min
Ratio
TENDL Threshold 1.2674 MeV
ENDFB8.0 Threshold 1.2672 MeV
Cross Section (milli-barns)
500
400
300
200
100
0
ENDFB8.0/TENDL
Ratio
10^0
10^-3
10^-6
10^-9
2
3
4
5
6
7
8
10^7
2
3
4
5
6
7
8
10^8
2
10
Incident Energy (eV)
52-Te-122


MAT 5231
MT= 54 (n,n') Level
Cross Section
52-Te-122
-100.0 To -4.892%
Max
Ratio
Min
Ratio
TENDL Threshold 1.3686 MeV
ENDFB8.0 Threshold 1.3682 MeV
Cross Section (milli-barns)
160
140
120
100
80
60
40
20
0
ENDFB8.0/TENDL
Ratio
10^0
10^-3
10^-6
10^-9
2
3
4
5
6
7
8
10^7
2
3
4
5
6
7
8
10^8
2
11
Incident Energy (eV)
52-Te-122


MAT 5231
MT= 55 (n,n') Level
Cross Section
52-Te-122
-98.92 To 557.0 %
Min
Ratio
Max
Ratio
TENDL Threshold 1.7615 MeV
ENDFB8.0 Threshold 1.7645 MeV
Cross Section (milli-barns)
80
60
40
20
0
ENDFB8.0/TENDL
Ratio
10^1
10^0
10^-1
10^-2
2 3 4 5 6 7 8 10^7 2 3 4 5 6 7 8 10^8 2
12
Incident Energy (eV)
52-Te-122


MAT 5231
(n,n') Continuum
Cross Section
52-Te-122
-63.73 To 2409. %
Max
Ratio
Min
Ratio
TENDL Threshold 2.6149 MeV
ENDFB8.0 Threshold 1.7645 MeV
Cross Section (barns)
2.0
1.5
1.0
0.5
0.0
ENDFB8.0/TENDL
Ratio
10^1
10^0
4
2
3
4
5
6
7
8
10^7
10^8
13
Incident Energy (eV)
52-Te-122


MAT 5231
(n,γ)
Cross Section
52-Te-122
-99.41 To 5847. %
Max Ratio
Min Ratio
TENDL
ENDFB8.0
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
14
52-Te-122


MAT 5231
(n,p)
Cross Section
52-Te-122
-100.0 To -23.84%
Min Ratio
Max Ratio
TENDL Threshold 1.2066 MeV
ENDFB8.0 Threshold 2.0000 MeV
Cross Section (milli-barns)
30
25
20
15
10
5
0
ENDFB8.0/TENDL
Ratio
10^0
10^-3
10^-6
2 3 4 5 6 7 8 10^7 2 3 4 5 6 7 8 10^8 2
15
Incident Energy (eV)
52-Te-122


MAT 5231
(n,d)
Cross Section
52-Te-122
-100.0 To 16.64 %
Min Ratio
Max Ratio
TENDL Threshold 5.8264 MeV
ENDFB8.0 Threshold 7.0000 MeV
Cross Section (milli-barns)
25
20
15
10
5
0
ENDFB8.0/TENDL
Ratio
10^0
10^-2
10^-4
10^-6
6 7 8 9 10^7 2 3 4 5 6 7 8 9 10^8 2
16
Incident Energy (eV)
52-Te-122


MAT 5231
(n,t)
Cross Section
52-Te-122
-100.0 To 554.4 %
Min Ratio
Max Ratio
TENDL Threshold 8.8478 MeV
ENDFB8.0 Threshold 10.000 MeV
Cross Section (milli-barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
17
52-Te-122


MAT 5231
(n,He-3)
Cross Section
52-Te-122
-98.49 To 513.6 %
Min Ratio
Max Ratio
TENDL Threshold 6.1263 MeV
ENDFB8.0 Threshold 9.0000 MeV
Cross Section (milli-barns)
1.6
1.2
0.8
0.4
0.0
ENDFB8.0/TENDL
Ratio
10^1
10^0
10^-1
10^-2
6 7 8 9 10^7 2 3 4 5 6 7 8 9 10^8 2
18
Incident Energy (eV)
52-Te-122


MAT 5231
(n,α)
Cross Section
52-Te-122
-100.0 To 1862. %
Min Ratio
Max Ratio
TENDL
ENDFB8.0 Threshold 100.00 keV
Cross Section (milli-barns)
25
20
15
10
5
0
ENDFB8.0/TENDL
Ratio
10^0
10^-3
10^-6
10^-5 10^-4 10^-3 10^-2 10^-1 10^0 10^1 10^2 10^3 10^4 10^5 10^6 10^7 10^8
19
Incident Energy (eV)
52-Te-122


MAT 5231
Hydrogen Production
Cross Section
52-Te-122
-100.0 To -14.38%
Min Ratio
Max Ratio
TENDL Threshold 1.2066 MeV
ENDFB8.0 Threshold 2.0000 MeV
Cross Section (barns)
2.5
2.0
1.5
1.0
0.5
0.0
ENDFB8.0/TENDL
Ratio
10^0
10^-3
10^-6
2 3 4 5 6 7 8
10^7
2 3 4 5 6 7 8
10^8
2
20
Incident Energy (eV)
52-Te-122


MAT 5231
Deuterium Production
Cross Section
52-Te-122
-100.0 To 16.61 %
Min Ratio
Max Ratio
TENDL Threshold 5.8264 MeV
ENDFB8.0 Threshold 7.0000 MeV
Cross Section (milli-barns)
350
300
250
200
150
100
50
0
ENDFB8.0/TENDL
Ratio
10^0
10^-2
10^-4
10^-6
6 7 8 9 10^7 2 3 4 5 6 7 8 9 10^8 2
21
Incident Energy (eV)
52-Te-122


MAT 5231
Tritium Production
Cross Section
52-Te-122
-100.0 To 554.4 %
Min Ratio
Max Ratio
TENDL Threshold 8.8478 MeV
ENDFB8.0 Threshold 10.000 MeV
Cross Section (milli-barns)
250
200
150
100
50
0
ENDFB8.0/TENDL
Ratio
10^2
10^0
10^-2
10^-4
9
10^7
2
3
4
5
6
7
8
9
10^8
2
22
Incident Energy (eV)
52-Te-122


MAT 5231
He-3 Production
Cross Section
52-Te-122
-98.49 To 513.6 %
Min Ratio
Max Ratio
TENDL Threshold 6.1263 MeV
ENDFB8.0 Threshold 9.0000 MeV
Cross Section (milli-barns)
350
300
250
200
150
100
50
0
ENDFB8.0/TENDL
Ratio
10^1
10^0
10^-1
10^-2
6 7 8 9 10^7 2 3 4 5 6 7 8 9 10^8 2
23
Incident Energy (eV)
52-Te-122


MAT 5231
He-4 Production
Cross Section
52-Te-122
-100.0 To 1862. %
Min Ratio
Max Ratio
TENDL
ENDFB8.0 Threshold 100.00 keV
Cross Section (milli-barns)
400
300
200
100
0
ENDFB8.0/TENDL
Ratio
10^0
10^-3
10^-6
10^-5 10^-4 10^-3 10^-2 10^-1 10^0 10^1 10^2 10^3 10^4 10^5 10^6 10^7 10^8
24
Incident Energy (eV)
52-Te-122


MAT 5231
Kerma total (eV-barns)
Cross Section
52-Te-122
13.74 To 9999. %
Max Ratio
Min Ratio
TENDL
ENDFB8.0
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
25
52-Te-122


MAT 5231
Kerma elastic
Cross Section
52-Te-122
-99.16 To 9999. %
Max
Ratio
Min
Ratio
TENDL
ENDFB8.0
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
26
52-Te-122


MAT 5231
Kerma non-elastic (all but mt2)
Cross Section
52-Te-122
580.8 To 9999. %
Max Ratio
Min Ratio
TENDL
ENDFB8.0
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
27
52-Te-122


MAT 5231
Kerma inelastic (mt51-91)
Cross Section
52-Te-122
1820. To 9999. %
Max Ratio
Min Ratio
TENDL Threshold 568.76 keV
ENDFB8.0 Threshold 568.67 keV
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
28
52-Te-122


MAT 5231
Kerma fission (mt18 or mt19-20-21-38)
Cross Section
52-Te-122
1820. To 9999. %
Max Ratio
Min Ratio
TENDL
ENDFB8.0
Cross Section (barns)
1.0
0.5
0.0
-0.5
-1.0
ENDFB8.0/TENDL
Ratio
10^12
10^9
10^6
10^3
10^-5 10^-4 10^-3 10^-2 10^-1 10^0 10^1 10^2 10^3 10^4 10^5 10^6 10^7 10^8
29
Incident Energy (eV)
52-Te-122


MAT 5231
Kerma capture (mt102)
Cross Section
52-Te-122
9999. To 9999. %
Max Ratio
Min Ratio
TENDL
ENDFB8.0
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
30
52-Te-122


MAT 5231
Total photon (eV-barns)
Cross Section
52-Te-122
9999. To 9999. %
Max Ratio
Min Ratio
TENDL
ENDFB8.0
Cross Section (Giga-barns)
50
40
30
20
10
0
ENDFB8.0/TENDL
Ratio
10^8
10^6
10^4
10^{-5} 10^{-4} 10^{-3} 10^{-2} 10^{-1} 10^{0} 10^{1} 10^{2} 10^{3} 10^{4} 10^{5} 10^{6} 10^{7} 10^{8}
31
Incident Energy (eV)
52-Te-122


MAT 5231
Total kinematic kerma (high limit)
Cross Section
52-Te-122
-91.79 To 2560. %
Max Ratio
Min Ratio
TENDL
ENDFB8.0
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
32
52-Te-122


MAT 5231
Dpa total (eV-barns)
Cross Section
52-Te-122
-91.78 To 2578. %
Max Ratio
Min Ratio
TENDL
ENDFB8.0
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
33
52-Te-122


MAT 5231
Dpa elastic (mt2)
Cross Section
52-Te-122
-92.25 To 7135. %
Max Ratio
Min Ratio
TENDL Threshold 740.10 eV
ENDFB8.0 Threshold 707.77 eV
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
34
Incident Energy (eV)
52-Te-122


MAT 5231
Dpa inelastic (mt51-91)
Cross Section
52-Te-122
-70.54 To 9999. %
Min
Ratio
TENDL Threshold 568.76 keV
ENDFB8.0 Threshold 568.67 keV
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
35
52-Te-122


MAT 5231
Dpa disappearance (mt102 -120)
Cross Section
52-Te-122
-84.03 To 9999. %
Max Ratio
Min Ratio
TENDL
ENDFB8.0
Cross Section (barns)
ENDFB8.0/TENDL
Ratio
Incident Energy (eV)
36
52-Te-122